




18-03-2024  
50400 >

 PIPE DIMENSION	DIA. 75 - 150 MM / 3" - 6"	 EXPANSION / EXTRACTION	60 MM / 2,4"
 SUPPLY HOSE	25 OR 50 METRES, 82 OR 164 FT	 ROTATION	360° CONTINUOUS ROTATION
 FLEXIBLE	45° - 90°	 GRINDS, MILLS AND CUTTS	PVC, LINER, CONCRETE, IRON, CAST IRON, STAINLESS STEEL

## Dancutter's Extremely Flexible Cutter

# DC SUPER FLEX

**DC SUPER FLEX** is Dancutter's extremely flexible cutter. It can move through several 90° bends in a 100 mm / 4" pipe and works effortlessly whether the pipe is straight or has bends. The flexibility of the DC SUPER FLEX makes it ideal for reopening laterals, and its robustness and durability let it easily remove concrete or other hard deposits from pipelines.

When you are cutting, milling, and grinding in pipes from 75 – 150 mm / 3" - 6" in., DC SUPER FLEX is the perfect solution, no matter if the pipe is made of PVC, concrete, cast iron or steel.

We also offer an extensive range of **cutting heads** for various purposes.



### Contact Information

Dancutter A/S  
Livøvej 1A DK-8800 Viborg  
  
Tel: +45 9651 2150  
info@dancutter.dk  
**dancutter.com**

### Technical support

If you experience problems with the cutter or if you have any technical questions, please write to **support@dancutter.dk**

### Order

If you need accessories for your cutter please write to **order@dancutter.dk**





18-03-2024  
50400 >

## SPECIFICATIONS

 AIR SUPPLY	650 L/MIN, 22 CFM	 POWER SUPPLY	110 / 240 VAC 
 AIR MOTOR	15000 RPM	 WEIGHT	25 M: 58 KG, 128 LB 50 M: 71 KG, 156.5 LB
 AIR PRESSURE	10 BAR, 145 PSI	 STAINLESS-STEEL FRAME	L: 1000 MM / 39.37" W: 500 MM / 19.69" H: 1030 MM / 40.55"

## Dancutter's Extremely Flexible Cutter

# DC SUPER FLEX

### Highlights

- ✓ 360° continuous rotation
- ✓ Stainless steel
- ✓ 12" colour display
- ✓ Extremely flexible in 45° and 90° bends
- ✓ Cuts, grinds, and mills in all materials
- ✓ User friendly
- ✓ Precise control
- ✓ Toolbox and centring tool with brushes are standard accessories

### Technical data

- ✓ Pipe diameter: 75 - 150 mm / 3" - 6" in
- ✓ DC SUPER FLEX can be operated by just one person using the control unit
- ✓ Control unit with 2 joysticks, a keypad with a 12" colour display. It features inlet and outlet sockets for connecting a video recorder, computer, external camera, or FPV headset
- ✓ The camera on the cutter has a spray nozzle that cleans the lens with air or washer fluid
- ✓ The DC SUPER FLEX comes with either a 25-metre or a 50-metre hose



### Standard and extra accessories for DC SUPER FLEX

We offer a versatile range of accessories and spare parts for your Dancutter solutions.

[dancutter.com](http://dancutter.com)

Authorised Representative in the United Kingdom: Mini-Cam Limited Unit 33, Ravenscraig Road, Little Hulton, Salford, M38 9PU.

© Copyright 2021 Dancutter A/S. Dancutter A/S is a Halma Company. Dancutter A/S, Livøvej 1, DK-8800 Viborg, +45 9651 2150, info@dancutter.dk, dancutter.com.  
In the event of the new product developments, Dancutter reserves the right to change the technical description without advance notice.