

6.0 DC SUPER FLEX

Dancutter's Extremely Flexible Cutter


This dynamic cutter can effortlessly move through several 90-degree bends in 100 mm pipes. Whether dealing with straight runs or intricate bends, the DC SUPER FLEX operates with unmatched precision.

The flexibility of the DC SUPER FLEX makes it ideal for re-opening laterals, and its robustness and durability let it easily remove concrete or other hard deposits from pipelines.

When you are cutting, milling, and grinding in pipes ranging from 75–150 mm, 3"–6" w/o centring tool set and up to 250 mm, 10" w/ centring tool set, regardless of the material – whether PVC, concrete, cast iron, or steel – the DC SUPER FLEX stands out as the perfect tool.



Specifications



PIPE DIAMETER

Dia. 75 – 150 mm, 3" – 6" w/o centring tool set.
Up to 250 mm, 10" w/ centring tool set



SUPPLY HOSE OPTIONS

25 or 50 metres, 82 or 164 ft



BENDS

45° - 90°



EXPANSION / EXTRACTION

60 mm - 2,4"



ROTATION

360° continuously



GRINDS, MILLS AND CUTS

Pvc, liner, concrete, iron, cast iron,
stainless steel

Technical support

If you experience problems with the cutter or if you have any technical questions, please write to support@dancutter.dk

Order

If you need spare parts or cutting heads, please write to order@dancutter.dk



Highlights

- Extremely flexible in 45° and 90° bends
- 360°-degree continuous rotation
- High-quality stainless-steel alloy
- 12" colour display
- Cuts, grinds, and mills in all materials
- User friendly
- Precise control
- Toolbox and centring tool with brushes are standard accessories

Technical data

Pipe diameter: 75 – 150 mm, 3" – 6" w/o centring tool set.
Up to 250 mm, 10" w/ centring tool set

DC SUPER FLEX can be operated by just one person

The DC SUPER FLEX comes with either a 25 m or a 50 m hose

The control unit features inlet and outlet sockets for connecting a video recorder, computer, external camera, or FPV headset (optional accessory)

12" colour display

Spray nozzle for cleaning the camera



AIR SUPPLY

650 l/min, 22 cfm



GRINDER

15000 rpm



AIR PRESSURE

Max 10 bar, 145 psi



POWER SUPPLY

110 / 240 VAC - LN 



WEIGHT

25 m: 58 kg, 128 lb/50 M: 71 kg, 156.5 lb



STAINLESS - STEEL FRAME

L: 1000 MM / W: 500 mm / H: 1030 mm
L: 39,37" / W: 19,69" / H: 40,55"

Standard and extra accessories for DC SUPER FLEX

We offer a versatile range of accessories and spare parts for your Dancutter solutions.

Get an overview on www.dancutter.com